



CALLA® Health Zone™

Square Lay-in & Tegular
smooth texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems



**24/7
DEFEND™**
Solutions for Healthier,
Safer Spaces

CONTAIN CLEAN PROTECT

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFLEX®
A New World of Choice
for Ceiling Systems

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

▲ Calla® Health Zone™ Square Tegular panels with Suprafine® 9/16" suspension system

Smooth, drywall-like finish panels that are water repellent; Meet USDA/FSIS, FGI and HIPAA guidelines plus Clean Room assemblies.
Offer both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Calla® Health Zone™ panels are part of the Sustain® portfolio and meet the most stringent sustainability compliance standards today
- Long-lasting water-repellency; Washable and Scrubbable
- Excellent combination of acoustical performance with exceptional noise blocking; NRC 0.80, CAC 38, and AC 170
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Bacteria-resistant surface
- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Impact-, Scratch-, and Soil-resistant; safe for use with disinfectants
- Clean Rooms up to ISO Class 5 (Class 100) (item 2231)
- Exceeds FGI Guidelines for acoustics and cleanability in general healthcare spaces
- Meets USDA/FSIS guidelines for use in food processing areas, kitchens, and clean room assemblies
- USDA-Certified Biobased Product – 91%
- 30-Year Limited System Warranty against visible sag, mold, and mildew and bacterial growth

COLOR



White
(WH)

DETAILS



1. Calla® Health Zone™ Square Lay-in
2. Calla® Health Zone™ Square Tegular
3. Calla Health Zone Square Tegular with Suprafine® 9/16" suspension system

TYPICAL APPLICATIONS

Clean Rooms (item 2231)
Healthcare:

- Patient rooms
- Treatment rooms
- Nurses' stations
- Emergency rooms
- Corridors
- Lavatories and restrooms
- Kitchen/food prep areas

Education
Office

CALLA® Health Zone™

Square Lay-in & Tegal
smooth texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 91%

Declare.

SUSTAIN®
High Performance
Sustainable Ceiling Systems

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC

76% RECYCLED
CONTENT

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

PB ONLY PB ONLY

VISUAL SELECTION

	Item No.	Dimensions (Inches)	
CALLA® Health Zone™	2230	24 x 24 x 1"	
15/16" Square Lay-in	2233	24 x 48 x 1"	
	2236	30 x 30 x 1"	
15/16" Square Tegal	2231	24 x 24 x 1"	
	2234	24 x 48 x 1"	
	2237	30 x 30 x 1"	
9/16" Square Tegal	2232	24 x 24 x 1"	
	2235	24 x 48 x 1"	
	2238	30 x 30 x 1"	

1" Thick – 15/16" Square Lay-in & 15/16" & 9/16" Square Tegal

Made-to-Order
Sizes

Visit the product
page online and see
"Configure an Item" to
verify capabilities. Questions? email
Techline@armstrongceilings.com

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

Width	Length
4" – 1-1/2"	12" – 72"
12" – 30"	4" – 72"
30-1/2" – 48"	4" – 24"

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics		Total Acoustics¹	Articulation Class	Fire Performance	Light Reflect*	Bio-Block+ Anti-Bacterial/ Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels		DURABILITY						Recycle Program 30-Yr Warranty
NRC	+ CAC *								NRC CAC	AC	Fog & Spray	Wipe	Water Repel	Wash*	Scrub*	Impact	
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
0.80 •	38 •	BEST ()))	170 •	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•
15/16" & 9/16" Square Tegular																	
N/A	N/A	N/A	N/A	Class A	0.85 •	+	•	•	•	•	•	•	•	•	•	•	•

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Advertised values for light reflectance, wash, scrub and scratch resistance are applicable to White panels only

SUSPENSION SYSTEMS

* CAC 29 achieved with Clean Room™ suspension system; not UL Classified for acoustics.

15/16"			1-1/2"		9/16"				
	Prelude®	Clean Room™ (Steel or Aluminum)		Clean Room (Steel or Aluminum)		Silhouette® 1/4" Reveal	Silhouette 1/8" Reveal	Suprafine®	Interlude® XL® HRC

NOTE: Clean Room Class 5 (Class 100) (item 2231) UL Classified for Acoustics on 15/16" suspension system only.

PHYSICAL DATA

Material

Wet-formed mineral fiber with acoustically transparent membrane

Surface Finish

Acoustically transparent membrane with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification

Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew

Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



Insulation Value

R Factor – 2.9 (BTU units)
R Factor – 0.445 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton

2230, 2231, 2232 – 1.0 lbs/SF; 40 SF/ctn
2233, 2234, 2235 – 1.0 lbs/SF; 48 SF/ctn
2236, 2237, 2238 – 1.0 lbs/SF; 50 SF/ctn

Minimum Order Quantity

1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/callahealthzone

BPCS-6028-1020

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2020 AWI Licensing LLC

Armstrong®
CEILING & WALL SOLUTIONS



MINERAL FIBER – Standard