

# DESIGNER™

## Square Lay-in & Tegal coarse texture



LEED® WELL | LBC

UP TO 42% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/ biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting/ materials

lighting quality

acoustics

Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

\$\$\$\$



Designer™ Lay-in panels with Prelude® XL 15/16" suspension system

Coarse-texture panels; economical option with standard acoustical performance.

### KEY SELECTION ATTRIBUTES

- Standard sound absorption
- Cost-effective
- Designer™ is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

### COLOR



### VISUAL SELECTION

| armstrongceilings.com/suspdwgs       | Susp. Dwg. | Item No. | Dimensions (Inches) |
|--------------------------------------|------------|----------|---------------------|
| DESIGNER™<br>15/16"<br>Square Lay-in | 1          | 735      | 24 × 24 × 5/8"      |
|                                      |            | 734      | 24 × 48 × 5/8"      |
| 15/16"<br>Angled Tegal               | 13         | 737      | 24 × 24 × 5/8"      |


### PERFORMANCE SELECTION

Dots represent high level of performance.

| UL Classified Acoustics | Total Acoustics <sup>1</sup> | Fire Performance | Light Reflect | Anti-Mold/Mildew | Sag Resistant | Certified Low VOC Emissions | Durability | Recycled Content | Recycle Program | Warranty |
|-------------------------|------------------------------|------------------|---------------|------------------|---------------|-----------------------------|------------|------------------|-----------------|----------|
| NRC + CAC =             |                              |                  |               |                  |               |                             |            |                  |                 |          |
| 0.55 30                 | N/A                          | Class A          | 0.81          | N/A              | Std           | *                           | Std        | Std              | *               | 1-Yr     |
| 0.55 30                 | N/A                          | Class A          | 0.81          | N/A              | Std           | *                           | Std        | Std              | *               | 1-Yr     |
| 0.55 33                 | N/A                          | Class A          | 0.81          | N/A              | Std           | *                           | Std        | Std              | *               | 1-Yr     |

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type A, Form A1.2, Pattern F; Fire Class A

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Insulation Value**  
R Factor – 1.5 (BTU units)  
R Factor – 0.26 (Watts units)

**1-Year Limited Warranty**  
Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
734 – 0.80 LBS/SF; 80 SF/CTN  
735, 737 – 0.80 LBS/SF; 64 SF/CTN

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
735M, 734M, 737M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.