



Catalog Number
Notes
Type

Contractor Select™

WSX Series

Wall Switch Sensor

The WSX family of wall switch occupancy sensors provide simple and cost-effective solutions for commercial and residential lighting control applications. The WSX family provides reliable sensing and dimming performance optimized for your space. All WSX family sensors have a modern low profile appearance, soft-click buttons, with small motion detection up to 20 ft (6.10 m), ideal for private offices, private restrooms, closets, copy rooms, or any other small enclosed space. The WSX Family of sensors are easy to program using the traditional push-button programming. Easy to install and aids in energy code compliance, the WSX family has a patented wiring method that enables them to function with or without a neutral connection. WSX units come pre-configured for wiring without a neutral; however, if a connection to neutral is required by code, contractors can convert the unit in seconds.

FEATURES:

- Digital Push-button programmable without removing cover plate - adjustable time delays & operating modes
- Compatible w/LEDs, electronic & magnetic ballasts, CFLs, & incandescents
- 100% passive detection, no potential for interference with other building systems
- Small motion detection to 20 ft
- Self-grounding mounting strap
- Device allows powering over ground or neutral connection (patent pending)
- Ultra low current leakage (<0.5 mA) when connected via ground
- Fully meets NEC 2011 Section 404.2C neutral requirements - no current leakage to ground when connected to neutral
- Line power and load wires are interchangeable - impossible to wire backwards (patented)
- Vandal resistant lens



Catalog Number	UPC	Description	Detection Type	Coverage	Voltage Type	Color	Voltage	Pallet Quantity
WSX WH	753573767527	Wall Switch	Passive Infrared (PIR)	1-Pole	Line	White	120 to 277V	100
WSX IV	820476070174	Wall Switch	Passive Infrared (PIR)	1-Pole	Line	Ivory	120 to 277V	100

More configurations are available. [Click here](#) or visit www.acuitybrands.com and search for WSX Series.



Specifications

INSTALLATION:

The WSX should be mounted with a single gang switch box.

LISTINGS:

CSA certified to US and Canadian safety standards.

For use in ambient operating temperatures ranging from -10°C to 60°C.


WARRANTY:

5-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Dimensions



WSX

All dimensions are inches (centimeters) unless otherwise indicated.